

Diaphragm Pumps

Engineered for Excellence



FLEX Series – Diaphragm Pump

Pump Type: Demand

Flow: 2.2 GPM

Pressure: 60 PSI

Valves: Viton

Diaphragm: Santoprene

Ports: 3/4" Quick Attach

Power: 12V – Wire Leads with 2-Pin Molded Connector, 115V AC Corded Plug

Weight: 6 lbs.

Packaging: Bulk Box, Retail Box

Shipping: 8 Per Carton Bulk, 8 Per Carton Retail

- 100% Factory Tested
- High Torque Motor for Superior Flow at Pressure
- Self-Priming
- Can be Run Dry
- Patented Adaptive Port Technology

BOX INCLUDES: Two Slide Adapters,
Three 5/8" Fittings and Two Port Adapters



Diaphragm Pumps

Performance Specifications

2.2 GPM Demand

PSI	GPM	AMPS
0	2.2	4.65
10	2	5.52
20	1.96	6.05
30	1.9	6.99
40	1.85	7.42
50	1.78	8.12

FLEX Series Diaphragm Pump Product Listing

Item #	GPM	PumpType	PSI	Valves	Diaphragm	Ports	Wire Leads
7822FS-201	2.2	Demand	60	Viton	Santoprene	3/4" Quick Attach	•

